



The Right Connection™

HOLEDALL® SWAGING MACHINE RANGE

Benefits Of Internal Expansion

Easy safe & consistent assembly

Virtual full - flow bore

Full 360° uninterrupted internal expansion

Secure - outperforms clamps & bands

Excellent sealing & retention between coupling & hose

Reduced turbulence through the hose

Fully complies with BSEN 1765/ BS:EN 1435/ EN: 14421

Reduced risk of bacteria traps in hygienic hose assemblies

Dixon Group Europe Ltd

350 Leach Place
Walton Summit Centre
Preston, Lancashire, PR5 8AS

T: +44(0)1772 323529

F: +44(0)1772 314664

W: www.dixoneurope.co.uk

E: enquiries@dixoneurope.co.uk

| Swaging Capacity: | Hydraulic Ram: | Hydraulic Unit: | Oil Reservoir: | Pressure Indication: | Electrical Power: | Operation: | Size: mm | Safety Features: |
|-------------------|----------------|-----------------|----------------|----------------------|-------------------|------------|----------|------------------|
|-------------------|----------------|-----------------|----------------|----------------------|-------------------|------------|----------|------------------|

TECHNICAL SPECIFICATION

T-20 IX



1"- 3" Nominal Bore, Threaded, Victaulic, Flanged, Hygienic Couplings etc.. Internal Swage

160mm Stroke x 20 ton pull @10,000psi (700bar)

Power Team
2 Stage
30cu.in/min.

4.5 litre capacity with sight glass

100mm diameter gauge
0-700 bar

Power Supply :
230 v,
1ph, 50Hz

Push - Button
Remote
Handset

345 x 200 x 205

CE Marked in accordance with European Legislation

T-50 IX



1"- 6" Nominal Bore, Threaded, Victaulic, Flanged, Hygienic etc.. Internal Swage

400mm Stroke x 52 ton pull @5,000psi (350bar)

Submerged
3/18 L/min
Gear/Piston
Pump
Assembly

70 litre capacity with sight glass

100mm diameter gauge
0-350 bar

Main Motor:
3Kw, Power
Supply :
380/415 v,
3ph, 50Hz

Push - Button
Remote
Handset

1000 x 550 x 785

CE Marked in accordance with European Legislation

T-100 IX



1"- 12" Nominal Bore, Threaded, Victaulic, Flanged, Hygienic etc.. Internal Swage

550mm Stroke x 100 ton pull @10,000psi (700bar)

Submerged
18 L/min
gear/Piston
Pump
Assembly

70 litre capacity with sight glass

100mm diameter gauge
0-700 bar

Main Motor:
4Kw, Power
Supply :
380/415 v,
3ph, 50Hz

Push - Button
Remote
Handset

1000 x 650 x 700

CE Marked in accordance with European Legislation

T-350



2"- 14" Nominal Bore, Specially developed for Swaging Rotary Drilling Hose Couplings Dual Swage

915mm Stroke x 188 ton pull and 354 ton push

4 Galls/min @ 3,500 psi
2 Galls/min @ 10,000 psi

100 litre capacity with sight glass

100mm diameter gauge
0-1000 bar
Digital Chart Recorder Available

Main Motor:
11Kw, Power
Supply :
380/415 v,
3ph,
50/60Hz

Push - Button
Remote
Handset

3600 x 2554 x 1016

CE Marked in accordance with European Legislation